

Multi-Use Products

High Quality, Durability and Reliability



▲ Shown longest to shortest: **Splice Chucks, Strand Chucks and Anchor Chucks**

- **Multi-use design offers economical solution for pre-casting and pre-stressing applications**
- **Bayonet cap features knurled finish for improved grip and easy opening**
- **Chuck and anchor components available separately for economical service and repair**
- **Engineered plating reduces corrosion and extends chuck life**
- **All wedge assemblies include o-ring retainer to reduce lost pieces and ease assembly**

▼ *SURE-LOCK® multi-use chucks and jaw assemblies are used by pre-cast/prestressed concrete plants to produce poles, slabs, walls, segments, T sections, beams and girders used in all types of construction.*



Photo: DNV/DAG-Systems Int'l.

Multi-Use Strand Chucks

Normally used at the stressing end of a bed. Bayonet cap offer less likelihood of damage to cap during tensioning.

- Includes cap, spring, wedge and body
- Easy opening, cleaning and inspection
- Replacement parts available



Multi-Use Splice Chucks

Two lengths of strand can be connected while maintaining the strength of a continuous length.

- Safely connects two strand sections



Multi-Use Anchor Chucks

Often used on the non-stressing end of a bed, these chucks are very economical with few components.

- Open chuck
- Simple and easy to use
- Most economical



Multi-Use Products

▼ Multi-Use Strand Chucks

Strand Size	Model Number	Jaw Assembly	Retaining Ring	Body	Cap	Spring	Weight (lbs)
5 mm	F1197	F197J	F1R	F1B	F1C	F1S	1.0
7 mm	F1276	F276J	F1R	F1B	F1C	F1S	1.0
1/4"	F1250	F250J	F1R	F1B	F1C	F1S	1.0
5/16"	F1312	F312J	F1R	F1B	F1C	F1S	1.0
11/32"	F1343	F343J	F1R	F1B	F1C	F1S	1.0
3/8"	F1375	F375J	F2R	F2B	F2C	F2S	2.0
7/16"	F1437	F437J	F2R	F2B	F2C	F2S	2.0
1/2"	F1500EL	F500JEL	F2R	F2B	F2C	F2SEL	2.0
9/16"	F1562	F562J	F3R	F3B	F3C	F3S	2.6
6/10"	F1600	F600J	F3R	F3B	F3C	F3S	2.6

SURE-LOCK®



Strand Sizes:

5 mm to 6/10 inch

Wedge Type:

2-part and 3-part

Coating Type:

Zinc plated

▼ Multi-Use Splice Chucks

Strand Size	Model Number	Jaw Assembly	Coupling	Body	Back Plate	Spring	Weight (lbs)
5 mm	F4197	F197J	F1CP	F9B	F1BP	F1S	2.5
7 mm	F4276	F276J	F1CP	F9B	F1BP	F1S	2.5
1/4"	F4250	F250J	F1CP	F9B	F1BP	F1S	2.5
5/16"	F4312	F312J	F1CP	F9B	F1BP	F1S	2.5
11/32"	F4343	F343J	F1CP	F9B	F1BP	F1S	2.5
3/8"	F4375	F375J	F2CP	F10B	F2BP	F2S	4.0
7/16"	F4437	F437J	F2CP	F10B	F2BP	F2S	4.0
1/2"	F4500EL	F500JEL	F2CP	F10B	F2BP	F7S	4.0
9/16"	F4562	F562J	F3CP	F11B	F3BP	F3S	6.0
6/10"	F4600	F600J	F3CP	F11B	F3BP	F3S	6.0

**Contact Precision-Hayes
972-287-2390**

Custom anchors and wedges are available to meet your unique stressing needs.



Accessories

A complete line of accessory components for wedge and anchor maintenance, such as cleaning brushes and wedge setters.



▼ SURE-LOCK® Multi-Use Anchor Chucks

Strand Size	Model Number	Jaw Assembly	Retaining Ring	Body
5 mm	F2197	F197J	F1R	F4B
7 mm	F2276	F276J	F1R	F4B
1/4"	F2250	F250J	F1R	F4B
5/16"	F2312	F312J	F1R	F4B
11/32"	F2343	F343J	F1R	F4B
3/8"	F2375	F375J	F2R	F5B
7/16"	F2437	F437J	F2R	F5B
1/2"	F2500GL	F500JEL	F2R	F5B
9/16"	F2562	F562J	F3R	F6B
6/10"	F2600	F600J	F3R	F6B